

h/p/cosmos performance diagnostics "pro"

h/p/cosmos pulsar 3p 4.0



[Illustration non-binding]

medical

pos.	order number	product description	price
01	cos05001100003	Running machine h/p/cosmos pulsar 3p 4.0 Running surface 190 x 65 cm, Speed 0 ... 40 km/h, Elevation -25 ... +25 %, Drive motor 3 kW with high-performance 3-phase power supply, 2 interface ports COM1 & COM2 for PC-, ECG, Ergospirometry-, Blood-pressure system or printer	
02	cos00097010035	2 Interface cable RS232, 10 m	
03	cos10170	Safety arch with chest belt and harness	
04	cos14825	h/p/cosmos sirius lactate test meter Measurement within 15 seconds, storage of 250 values, interface for the PC (cable optional)	
05	cos14827	h/p/cosmos sirius lactate test strips, box with 72 test strips plus control-solution	
06	cos11657	Startset consumables „lactate“ incl. Latex gloves, size M, box with 100 pieces [cos11351], Kidney-dish, plastic [cos11355], Disinfectant spray, 250 ml [cos11352], Disposable lancets, sterile, box 200 pieces [cos11652], Plaster, box 420 pieces [cos11356], Swabs, 1000 pieces [cos11353], MEDI-Box (lancets collector) [cos11930]	
07	cos14708	Software h/p/cosmos para analysis 2.0 "professional" - sports medical evaluation software with integrated treadmill control software and training plan	
08	cos14970	h/p/cosmos satellite PC med - medical PC mini-tower, Windows XP incl. 19" LCD Monitor, keyboard, mouse, CD-ROM writer, FireWireCard, colour laser printer and PC-trolley, medical PC according to MDD & IEC 60601-1	
09	cos10223	Potential equalization cable, 5 m (required for medical systems)	
10	cos10179	Transport in cardboard box (assembled or part-assembled), installation & instruction included	

System h/p/cosmos performance diagnostics "professional"

E & OE. Subject to alterations without prior notice. System- and Software-training as well as workshops on request. Special accessories and custom made running machines for special applications on request. Manufacturer: h/p/cosmos sports & medical gmbh, Am Sportplatz 8, DE 83365 Nussdorf-Traunstein / Germany, phone + 49 / 8669 / 86 42 0, fax + 49 / 8669 / 86 42 49

sales@h-p-cosmos.com www.h-p-cosmos.com

running machine:	h/p/cosmos pulsar 3p 4.0 treadmill ergometer with user terminal (display & keyboard) stand-alone & remote control via RS232
applications:	running for sports, sports medicine, cardiology, stress tests & medicine
running surface:	length 190 cm / 74.83", width 65 cm / 25.59", access height 22 cm - special size on request - shock load reduction for the joints - belt surface with non slippery material - max. permissible load: 200kg (440 lbs)
speed range:	0 ... 40.0 km/h / 0 ... 1 1.1 m/sec. / 0 ... 25.0 mph) special speed up to 45 km/h on request
acceleration:	7 levels (in 3...131 sec. from 0 to max. speed) also for deceleration
elevation:	-25 ... 25 % (0...14°) adjustable electr., resolution 0.1% special elevation on request, electronic motor break system prevents from accelerating when running at max. elevation
running direction:	switch for reversing running belt direction, safety-harness required for reverse
motor system:	3.0 kW (4.1 HP) 3phase A.C. motor (maintenance free)
power transmission:	Poly-V-Belt drive (very quiet operation)
safety systems:	CE0123, MDD, Guideline 93/42 EEC for med. devices IEC EN 60335-1 (VDE 0700); IEC EN 60601-1 (VDE 0750) IEC EN 60601-1-2 (EMC approval); IEC EN 60601-1-4 VDE 0701; VDE 0751; EN 957-1; EN 957-6; emergency-off-switch (mains cut), Potential-Equalization Transformer for Potential-Isolation from the mains.
display(resolutions):	6 LCD displays, 4 LED for operation mode, 20 LEDs for display of units & profile no, & steps, etc. speed (0.1 km/h or m/sec or m/min or mph), time (00:00) in hours, minutes & seconds, elevation (0.1% / °) distance (1 meter ... 999.9 km or miles), METS (1 MET) program step/number, energy (1 kJ/kcal), fitness index(1) power (1 Watt), heart rate (1 bpm/beat per minute)
heartrate monitoring:	POLAR wireless, 1-channel receiver, ECG-accurate, measuring & display beat to beat
heartrate control:	automatic control of speed & elevation according to programmed target heart rate („cardio mode“)
interface digital:	2x RS232 COM1 + 2 incl. PC-, CosCom-, Blood-Pressure-Monitor-, ECG-, Ergospirometry- & series printer protocol
programs:	20 programs / profiles - 6 exercise profiles (scalable, 131 variations) - 10 test profiles (UKK Walktest, Cooper, Conconi, Graded Test etc.) - 4 free defineable profiles, 10 steps each
free PC software:	h/p/cosmos para control for display & remote control. h/p/cosmos para graphics for monitoring, recording & control incl. 1 RS 232 interface connection cable 5m
colour of frame:	grey aluminium RAL 9007 (powder coated), other colours available on request
handrails:	steel tube handrails on both sides, frontbar handrail
voltage supply:	380/420 Volt, 50/60 cycles (Hz), 3 phase AC, 20 Amps special voltage supply available on request
size of frame:	length 250 cm / 98.42", width 105 cm / 41.34", height 146 cm / 57.47"
weight:	approx. 450 kg / 990 lbs

Further details and accessories on request.

E & OE. Subject to alterations without prior notice.

Authorised h/p/cosmos dealer